

## Refrigerated



## Blown air deli - CARIB72.9

### CARIB72.9

Caribbean refrigerated blown air delis are part of the most versatile range of standard modular countering in the market place. They provide the basis for all types of counter layouts in different finishes to suit any location. The versatility of Caribbean counters allows its use across all market sectors. Principal sectors include:- Schools and colleges, hospitals, Business and industry, hotels, restaurants and licensed premises. Enclosed to front models Model No: CARIB72.912DL/SF - 1206mm long Model No: CARIB72.916DL/SF - 1606mm long Model No: CARIB72.916SF - 1906mm long Picture shows CARIB72.912DL unit finished in Ocean Blue plastic coated steel

## Specifications

**Dimensions:** Model ----- Dimensions ----- loading CARIB72.912 --- 1206 x 777 x 900mm high ---  
---1.6kW CARIB72.916 --- 1606 x 777 x 900mm high ---2.1kW CARIB72.919 --- 1906 x 777 x 900mm high ---  
**2.4kW Refrigerant:** R452a - zero ODP and low GWP refrigerant **Operating Conditions:** Designed to comply with the operating requirements of EN ISO 23953 - 2:2005 Performance level M1 (-1°C to + 5°C) in Climate class 3 (25°C 60% RH 0.2m/s) In use Victor refrigerated blown air delis will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C - 50% Relative Humidity

**Construction** Top: Stainless Steel, Exterior: Colour plastic coated steel or Stainless steel, Interior: Stainless Steel. **Well Dimensions & Capacity** 1206 model - 975 x 530 x 170mm - 3 x GN1/1 x 100mm deep 1606 model - 1305 x 530 x 170mm - 4 x GN1/1 x 100mm deep 1906 model - 1635 x 530 x 170mm - 5 x GN1/1 x 100mm deep

## Features

### Standard Features:

- 304 Stainless steel well - 170mm deep
- Load line indicator at 100mm to assist in the safe presentation of food
- Accepts GN1/1 gastronorm containers up to 100mm deep.
- Completely removable well giving easy access for cleaning and maintenance.
- Microprocessor controlled with automatic defrost & condense handling system.
- 1.5mm stainless steel tops with radius front & rear.
- Rear operator's side finished in stainless steel with radius corners.
- Stainless steel interior with radius rear corners.
- Four x 100mm swivel castors two braked.

### Extras:

- [Gantries](#)
- [Tray slides](#)
- [Kick-plinths](#)
- [Push bar](#)
- [Choice of colour finish](#)
- Height adjustable feet instead of castors

## Downloads



- [Operating Manual](#)