

## Refrigerated



## Blown air multi-tier - CARIB73.7

### CARIB73.7

Caribbean refrigerated multi-tiers are part of the most versatile range of standard modular countering in the market place. They provides the basis for all types of counter layouts in different finishes to suit any location. The versatility of Caribbean counters allow its use across all market sectors. Principal sectors include:- Schools and colleges, hospitals, Business and industry, hotels, restaurants and licensed premises

Rear door

**models** Model No: CARIB73.712 - 1206mm long  
Model No: CARIB73.716 - 1606mm long Model No:

CARIB73.719 - 1906mm long **Solid back models**

Model No: CARIB73.712W - 1206mm long Model No:

CARIB73.716W - 1606mm long Model No:

CARIB73.719W - 1906mm long

Picture shows

*CARIB73.716 rear door version finished in Ocean*

*Blue plastic coated steel with optional slide on kick-plinth*

## Specifications

**Dimensions:** Model ----- Dimensions ----- loading CARIB73.712 --- 1206 x 700 x 1600mm  
high --- 2.6kW CARIB73.716 --- 1606 x 700 x 1600mm high --- 3.0kW CARIB73.719 --- 1906 x 700 x 1600mm  
high --- 3.4kW *Wall units are 150mm deeper - 850mm* **Refrigerant:** R452a - zero ODP and low GWP  
refrigerant **Operating Conditions:** Designed to comply with the operating requirements of EN ISO 23953 –  
2:2005 Performance level M1 (-1°C to + 5°C) in Climate class 3 (25°C 60% RH 0.2m/s) 220V/240V 1 phase 50Hz  
Cable: 2 metres with 13 amp plug fitted 1906mm models fitted with cable and 16 amp commando plug  
**Construction** Top: Stainless Steel, Exterior: Colour plastic coated steel or Stainless steel, Interior:  
Stainless Steel. **Well Dimensions** 1206 model - 980 x 480 x 170mm 1606 model - 1300 x 480 x 170mm 1906 model  
- 1625 x 480 x 170mm

## Features

### Standard Features:

- Open fronted display cabinets achieves a balanced air temperature throughout the cabinet of between 2Â°C & 5Â°C in ambient temperatures up to 27Â°C at a relative humidity of 50%.
- Microprocessor based temperature control with automatic defrost and condensate handling system.
- Three height adjustable and removable shelves for flexibility of display.
- Illuminated display via integral fluorescent lighting.
- Supplied on castors with height adjustable levelling feet for stability.
- Double glazed rear hinged doors or solid back.
- 304 grade stainless steel top and well.
- Ambient under 1600mm & 1900mm rear hinged door models.

### Extras:

- [Tray slides](#)
- [Kick-plinths](#)
- [Push bar](#)
- [Choice of colour finish](#)
- Night Blinds

## Downloads



- [A Operating Manual](#)