

General Purpose - Plain Top



2 x GN1/1 with gantry- HC20MSG

HC20MSG

GN1/1 gastronorm compatible heated unit ideal for general purpose usage in all catering establishments, residential care homes, pubs, hotels, cafes, schools & colleges.

Specifications

Dimensions: External: 945 x 670 x 900mm - includes 65mm for push bar Internal: 740 x 545 x 4500mm Weight:
Electrical Connection 220V/240V, 1 phase 50Hz, 1.5kW loading, 6.3Amps approx Cable: 2 metres with 13
amp plug fitted
Construction Top: Stainless Steel, Exterior: Stainless Steel, Interior: Stainless
Steel. **Capacity** Hot cupboard: 36 plated meals, 258 10" plates

Features

Standard Features:

- Four x 100mm swivel castors two braked
- Top level recessed adjustable thermostat controls to hot cupboard.
- Robust push/pull bar. Can be fitted to either end or removed
- Curly cable with plug park.
- Digital temperature display.
- Fully GN1/1 gastronorm compatible.
- Two removable shelves & supports.
- Top hung sliding door with zero dirt traps to front edge.
- Removable element cover to maximise access for cleaning.
- Satin finish stainless steel interior with internal radius corners.
- Double skin construction providing coolwall exterior for safe & efficient operation.

Quartz heated gantry - 520mm high.

- Two x 300W operator changeable quartz heat lamps.
- Toughened curved glass overshelf and sneeze screen.
- 38mm dia. Stainless steel gantry arms.

Extras:

- Height adjustable legs in place of castors.
- Corner Bumpers
- Additional push bar
- Additional shelves
- Tray slides

Downloads



[Operating Manual](#)