

## Refrigerated



## Blown air well - JBA

### JBA

GN1/1 gastronorm compatible blown air refrigerated mobile salad well. Ideal for general purpose usage in all catering establishments, schools & colleges, residential care homes, pubs, hotels and cafes Model No: JBA30 - 1205mm long Model No: JBA40 - 1535mm long Model No: JBA50 - 1860mm long Picture shows JBA40 unit finished in solent blue plastic coated steel with optional GANCG40L gantry and TS40 trayslide

## Specifications

**Dimensions:** Model - - - - - Dimensions - - - - - loading JBA30 - - - 1205 x 670 x 900mm high - - - - - 1.6kW JBA40 - - - 1535 x 670 x 900mm high - - - - - 2.1kW JBA50 - - - 1860 x 670 x 900mm high - - - - - 2.4kW  
Standard counter top height is 900mm, JBA30 units can be manufactured with a reduce height of 850 or 875mm if required.

**Electrical Connection** 220V/240V 1 phase 50 Hz. Cable: All unit are fitted with two metres of cable and single 13 amp plug.

**Refrigerant:** R452a - zero ODP and low GWP refrigerant

**Operating Conditions:** Designed to comply with the operating requirements of EN ISO 23953 – 2:2005  
Performance level M1 (-1°C to + 5°C) in Climate class 3 (25°C 60% RH 0.2m/s) In use these units will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C – 50% Relative Humidity.

**Construction** Top: Stainless steel, Exterior: Coloured plastic coated steel or stainless steel, Interior: Stainless steel.

**Well Dimensions & Capacity** 1205 model – 975 x 530 x 170mm – 3 x GN1/1 x 100mm deep  
1535 model – 1305 x 530 x 170mm – 4 x GN1/1 x 100mm deep 1860 model – 1635 x 530 x 170mm – 5 x GN1/1 x 100mm deep

## Features

### Standard Features:

- 304 grade stainless steel well - 170mm deep
- Load line indicator at 100mm to assist in the safe presentation of food
- Accepts GN1/1 gastronorm containers up to 100mm deep.
- Completely removable well giving easy access for cleaning and maintenance.
- Microprocessor controlled with automatic defrost & condense handling system.
- Rear operator's side finished in stainless steel.
- Open ambient cupboard to rear - 1535 & 1855mm units only
- Four x 100mm swivel castors two braked.

### Options:

- [Gantries](#)
- [Tray slides](#)
- [Kick-plinths](#)
- [Push Bars](#)
- [Corner Bumpers](#)
- [Drop down end shelf](#)
- [Choice of colour finish](#)
- Height adjustable feet instead of castors

## Downloads



- [Product Leaflet](#)