

General Purpose - Refrigeration

RW30MSG

RW30MSG

GN1/1 gastronorm compatible blown air refrigerated mobile salad well. Ideal for general purpose usage in all catering establishments, schools & colleges, residential care homes, pubs, hotels and cafes

Specifications

Dimensions: high - - - - - 1.6kW	Model - - - - - Dimensions - - - - - loading RW30MSG - - - 1205 x 650 x 900mm		
metres of cable and single 13 amp plug.	Electrical Connection 220V/240V 1 phase 50 Hz. Cable: All unit are fitted with two		
Conditions: level M1 (-1°C to + 5°C) in Climate class 3 (25°C 60% RH 0.2m/s) In use these units will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C – 50% Relative Humidity.	Refrigerant: R404a CFC free refrigerant	Operating	
Stainless steel.	Construction Top: Stainless steel, Exterior: Stainless steel, Interior:		
deep	Well Dimensions & Capacity 1205 model – 975 x 530 x 170mm – 3 x GN1/1 x 100mm		

Features

Standard Features:

- L.E.D. illuminated gantry with toughened curved glass sneeze screen/over shelf
- 304 grade stainless steel well - 170mm deep
- Load line indicator at 100mm to assist in the safe presentation of food
- Accepts GN1/1 gastronorm containers up to 100mm deep.
- Completely removable well giving easy access for cleaning and maintenance.
- Microprocessor controlled with automatic defrost & condense handling system.
- Rear operator's side finished in stainless steel.
- Four x 100mm swivel castors two braked.

Options:

- [Tray slides.](#)
- [Push Bars.](#)
- [Corner Bumpers.](#)
- Height adjustable feet instead of castors