

General Purpose - Refrigeration



RW30MSG

RW30MSG

GN1/1 gastronorm compatible blown air refrigerated mobile salad well. Ideal for general purpose usage in all catering establishments, schools & colleges, residential care homes, pubs, hotels and cafes.

Specifications

Dimensions: Model ----- Dimensions ----- loading RW30MSg --- 1205 x 650 x 900mm high
----- 1.6kW **Electrical Connection** 220V/240V 1 phase 50 Hz. Cable: All unit are fitted with two metres of cable and single 13 amp plug. **Refrigerant:** R452a - zero ODP and low GWP refrigerant

Operating Conditions: Designed to comply with the operating requirements of EN ISO 23953 – 2:2005
Performance level M1 (-1°C to + 5°C) in Climate class 3 (25°C 60% RH 0.2m/s) In use these units will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C – 50% Relative Humidity. **Construction** Top: Stainless steel, Exterior: Stainless steel, Interior: Stainless steel. **Well Dimensions & Capacity** 1205 model – 975 x 530 x 170mm – 3 x GN1/1 x 100mm deep

Features

Standard Features:

- L.E.D. illuminated gantry with toughened curved glass sneeze screen/over shelf
- 304 grade stainless steel well - 170mm deep
- Load line indicator at 100mm to assist in the safe presentation of food
- Accepts GN1/1 gastronorm containers up to 100mm deep.
- Completely removable well giving easy access for cleaning and maintenance.
- Microprocessor controlled with automatic defrost & condense handling system.
- Rear operator's side finished in stainless steel.
- Four x 100mm swivel castors two braked.

Options:

- [Tray slides.](#)
- [Push Bars.](#)
- [Corner Bumpers.](#)
- Gn1/1 cradle
- Height adjustable feet instead of castors

Victor Manufacturing Limited

Lonsdale Works, Gibson Street, Bradford, BD3 9TF, West Yorkshire, England
Tel: +44 (0)1274 722125 Email: email@victormanufacturing.co.uk
Copyright © 2020 Victor Manufacturing Limited