

General Purpose - Refrigeration

RW40MSG

RW40MSG

GN1/1 gastronorm compatible blown air refrigerated mobile salad well. Ideal for general purpose usage in all catering establishments, schools & colleges, residential care homes, pubs, hotels and cafes.

Specifications

Dimensions: high - - - - - 2.1kW	Model - - - - - loading RW40 MSG- - - 1535 x 650 x 900mm		
metres of cable and single 13 amp plug.	Electrical Connection	220V/240V 1 phase 50 Hz. Cable: All unit are fitted with two	
Conditions: level M1 (-1°C to + 5°C) in Climate class 3 (25°C 60% RH 0.2m/s) In use these units will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C – 50% Relative Humidity.	Refrigerant:	R404a CFC free refrigerant	Operating
Stainless steel.	Construction	Top: Stainless steel, Exterior: Stainless steel, Interior:	
	Well Dimension & Capacity	1535 model – 1305 x 530 x 170mm – 4 x GN1/1 x 100mm deep	

Features

Standard Features:

- L.E.D. illuminated gantry with toughened curved glass sneeze screen/over shelf
- 304 grade stainless steel well - 170mm deep
- Load line indicator at 100mm to assist in the safe presentation of food
- Accepts GN1/1 gastronorm containers up to 100mm deep.
- Completely removable well giving easy access for cleaning and maintenance.
- Microprocessor controlled with automatic defrost & condense handling system.
- Rear operator's side finished in stainless steel.
- Open ambient cupboard to rear - 1535
- Four x 100mm swivel castors two braked.

Options:

- [Tray slides.](#)
- [Push Bars.](#)
- [Corner Bumpers.](#)
- Height adjustable feet instead of castors

Victor Manufacturing Limited

Lonsdale Works, Gibson Street, Bradford, BD3 9TF, West Yorkshire, England
Tel: +44 (0)1274 722125 Email: email@victormanufacturing.co.uk
Copyright © 2014 Victor Manufacturing Limited