

# Victor

## CARIBBEAN REFRIGERATED FOOD SERVICE MODULES (2010 MODELS)

### MODEL NUMBERS

CARIB72.412 CARIB72.412SY CARIB72.412DL CARIB72.412HD CARIB72.412SS CARIB72.412SF CARIB72.412CC	CARIB72.419 CARIB72.419SY CARIB72.419SS CARIB72.419SF CARIB72.419CC	CARIB72.916SY CARIB72.916DL CARIB72.916HD CARIB72.916SS CARIB72.916SF	CARIB72.212 CARIB72.212DB CARIB72.212IS CARIB72.212IF  CARIB72.216 CARIB72.216DB CARIB72.216IS CARIB72.216IF  CARIB72.219 CARIB72.219DB CARIB72.219IF	CARIB73.712 CARIB73.716 CARIB73.719  CARIB73.712W CARIB73.716W CARIB73.719W  CARIB72.712 CARIB72.716 CARIB72.719  CARIB72.712W CARIB72.716W CARIB72.719W
CARIB72.416 CARIB72.416SY CARIB72.416DL CARIB72.416HD CARIB72.416SS CARIB72.416SF CARIB72.416CC	CARIB72.912SY CARIB72.912DL CARIB72.912HD CARIB72.912SS CARIB72.912SF	CARIB72.919SY CARIB72.919SS CARIB72.919SF		

Thank you for buying a Victor Unit. We hope and expect that you will get many years of satisfactory use from your purchase.

In order to achieve the best results from your equipment please read, and follow, the installation, operating, cleaning and maintenance instructions below. Failure to follow them may affect the warranty.

### 1. UNPACKING AND ASSEMBLY

All protective coating used on stainless steel surfaces of the hot cupboard must be removed. The exposed surfaces can then be wiped clean with a damp cloth, using a mild detergent or soap if necessary.

**DO NOT USE ANY ABRASIVE MATERIAL OR FORM OF BLEACH FOR CLEANING PURPOSES.**

Please see cleaning section of this manual.

STATIC MODELS: Position the unit where it is to be used and ensure that it is level. This is achieved by adjusting the feet, turning clockwise to raise the unit and anticlockwise to lower the unit.

MOBILE MODELS: Four Castors are fitted, two of which are braked.

### 2. INSTALLATION

Position the appliance where it is to be used and ensure that it is level.

**Do not** site the appliance in the immediate vicinity of a heat source

Do not position the appliance so as to obstruct air vents on either the operator or customer sides of the appliance. Adequate airflows are vital to the correct functioning of the refrigeration system. Avoid placing the appliance in areas subject to strong draughts or under air conditioning systems. Avoid areas subject to high humidity (i.e. Conservatories) as the appliance will act as a de-humidifier, and create excessive amounts of water.

The appliance is fitted with either: a 13 Amp fused plug which requires connection to a suitable 13 Amp socket outlet, or (in the case of the CARIB73.719, CARIB73.719W, CARIB72.719 & CARIB72.719W); a 16 Amp plug which requires connection to a suitably protected 16 Amp socket. All models are suitable for 230 – 240V A.C. supply only. Ensure that the electricity supply is as stated on the model's data plate.

**IMPORTANT: If the unit you have purchased is not fitted with either a 13 Amp or 16 Amp plug and lead, this model will need to be connected to the mains via a suitable isolating switch by a qualified electrician and wired in accordance with the current edition of the I.E.E wiring regulations, ensuring the electricity supply is as stated on the data plate.**

**Important:** Wires in the mains lead are coloured in accordance with the following code:

<b>Green and Yellow</b>	-	<b>Earth</b>
<b>Blue</b>	-	<b>Neutral</b>
<b>Brown</b>	-	<b>Live</b>

**Warning:** This appliance must be earthed, do not touch internal wiring.

As the colours of the wires in the mains lead on this appliance may not correspond with the coloured markings identifying the terminals in your plug, proceed as follows:

- (a) The wire which is coloured green and yellow must be connected to the terminal in the plug, which is marked with letter **E** or the sign  $\perp$ .
- (b) The wire which is coloured blue must be connected to the terminal which is marked with the letter **N** or is coloured black.
- (c) The wire which is coloured brown must be connected to the terminal which is marked with the letter **L** or is coloured red.

### **3. USE AND BEST PERFORMANCE**

**BLOWN AIR WELL / DECK** (Where purchased)

**THE WELL IS DESIGNED TO MAINTAIN FOOD PLACED IN THE WELL AT BETWEEN 3° AND 5°C IN AMBIENT TEMPERATURES OF UP TO 25°C AND RELATIVE HUMIDITIES UP TO 60%;**

**FOOD PLACED IN THE WELL MUST BE AT OR BELOW THIS TEMPERATURE, BEFORE BEING PLACED IN THE WELL.**

The refrigeration system is operated by a green on / off switch marked 'REFRIGERATION', which will illuminate when the refrigeration is switched on.

The refrigeration system is controlled by a microprocessor control which is factory set and requires No adjustment, the digital display will show the air temperature within the well, not the food temperature. Other buttons on the controller are of no consequence to the user and are for factory or service engineer use only.

To obtain the best performance, the following procedure is suggested:

- (a) Switch on the refrigeration system via the switch located on the control panel.
- (b) Depending on the ambient temperature, allow the well approximately 30 minutes to reach the required temperature.
- (c) Load the well as required, be careful not to over pack the well and restrict airflows between the front and rear vents of the well as this will affect the efficiency of the refrigeration system. Do not fill above the "Load Lines" (where marked on the sides of the unit).

All refrigeration systems frost up when operating. Your appliance has a microprocessor control, programmed to defrost periodically. No manual defrost is required. The refrigeration system will automatically defrost every 2 hours for approximately 20 minutes. The controller will display 'def' during the defrost cycle and will then show 'rec' when resuming after defrost. Water collected from the defrost operation is automatically evaporated.

Please remember the refrigeration system is not designed to chill food, but is designed to maintain it at a satisfactory temperature before serving.

**MULTI-TIER DISPLAY (Where purchased)**

**THE DISPLAY IS DESIGNED TO MAINTAIN FOOD PLACED IN THE DISPLAY AT BETWEEN 3° AND 5°C IN AMBIENT TEMPERATURES OF UP TO 25°C WITH A RELATIVE HUMIDITY OF 60%; FOOD PLACED IN THE WELL MUST BE AT OR BELOW THIS TEMPERATURE, BEFORE BEING PLACED IN THE WELL.**

The refrigeration system is operated by a green on / off switch positioned to the left of the digital display, which will illuminate when the refrigeration is switched on. The lighting is controlled by an adjacent green on / off switch. See "gantry" section below for method of replacing fluorescent lamps.

The refrigeration system is controlled by a microprocessor control which is factory set and requires No adjustment, the digital display will show the air temperature within the well, not the food temperature. Other buttons on the controller are of no consequence to the user and are for factory or service engineer use only.

To obtain the best performance, the following procedure is suggested:

- (a) Switch on the refrigeration system via the switch located on the control panel.
- (b) Depending on the ambient temperature, allow the display approximately 30 minutes to reach the required temperature.

- (c) Load the display as required, be careful not to over pack the display and restrict airflows between the front and rear vents of the display as this will affect the efficiency of the refrigeration system.

All refrigeration systems frost up when operating. Your appliance has a microprocessor control, programmed to defrost periodically. No manual defrost is required. The refrigeration system will automatically defrost every 2 hours for approximately 20 minutes. The controller will display **def'** during the defrost cycle and will then show **'rec'** when resuming after defrost. Water collected from the defrost operation is automatically evaporated.

Please remember the refrigeration system is not designed to chill food, but is designed to maintain it at a satisfactory temperature before serving.

#### **TRAY SLIDE** (Where purchased)

Your appliance may be fitted with a tray slide which can be either fixed or drop down. If the drop down style has been purchased, it can be lowered to enable easy repositioning of the unit. The tray slide can be lowered by following the following procedure:

- (a) Remove all square nuts that are visible on the underside of the tray slide brackets, and remove the pins through the brackets.
- (b) Standing in front of the unit, pull the tray slide forward about 40mm.
- (c) The tray slide will now drop down to a vertical position.
- (d) Reverse this process to enable use, ensuring that all pins and nuts are refitted.

#### **GANTRY** (Where purchased)

The gantry will be fitted with a fluorescent tube, this is controlled by an on/off switch. The lamp is replaceable. Please follow the following procedure:

#### **Replacing Fluorescent Lamp:**

- (a) Turn off power to the unit. If the bulb has just failed it may be HOT.
- (b) Grip the bulb at both ends, near the connectors and twist the bulb approximately 90° Degrees.
- (c) Gently pull the bulb out of the connectors.
- (d) Reverse this process to fit, ensuring that the bulb is held firmly and correctly within the connectors before releasing.

#### 4. CLEANING

##### **SWITCH OFF THE UNIT AT THE MAINS BEFORE CLEANING.**

Stainless steel surfaces will give you many years of trouble-free use as long as you follow a few simple rules. If it appears to mark do not worry, it is usually not the steel but something deposited on it which has stained.

**Do wash all surfaces before use.** You should use a damp cloth and a mild detergent or soap, or similar cleaner. Always rinse well with clean water and dry the surface with a soft cloth. Clean regularly when in use. Do use soft cloths, nylon or bristle brushes.

**Do not use** metal scrapers, wire brushes or wire wool pads as they can scratch the steel. Do take care when handling sharp objects as they can scratch the surface of stainless steel. Any scratches on stainless steel will blend together over a period of time and become less noticeable with age. There is no detriment to the corrosion resistance or general performance of the material.

**Do not use** bleach for cleaning purposes (remember dishwasher powders, sterilising agents and similar products all contain chlorides). If used, black pit marks or other such effects may appear and permanent damage may be caused. If used inadvertently rinse immediately with clean water.

**Do not splash the unit with bleach when cleaning around the counter.** If you do, rinse the surface immediately with clean water thoroughly.

**Do not allow** corrosive foodstuffs such as fruit juices, vinegar, mustards, pickles, mayonnaise, etc., to remain on stainless steel for long periods. Wash and rinse away.

**Do not** leave steel objects or utensils standing on the stainless steel surfaces for long periods. They can rust and leave marks. After cleaning with detergent always remove residues with a wet cloth and wipe dry, if left they can have an etching effect on the surface.

**CORRECTLY APPLIED, THE ABOVE INSTRUCTIONS WILL RESULT IN CONTINUOUS GOOD LOOKS!**

#### 5. MAINTENANCE & SPARES

**IMPORTANT:** You must disconnect the appliance from the mains before removing any components which have been fastened using screws, etc.

##### **Routine Maintenance**

The refrigeration system WILL pick up dust from the air which builds up on certain parts, causing them to lose effectiveness. It is important to call a service engineer to examine, and clear, the system as necessary or every 6 months.

To access the condenser for cleaning remove the front grill must be removed. Clear condenser with a brush and clean away the dust.

You should have the various items in your unit tested for electrical safety at least once a year as required by the Electricity at Work Regulations.

Spare parts are available for all models of equipment. These can be obtained by contacting your distributor.

When ordering any spare parts always quote the model and serial number.

PLEASE USE THE BOX PROVIDED BELOW TO RECORD YOUR MODEL AND SERIAL NUMBER FOR FUTURE INFORMATION, THIS CAN BE FOUND ON THE DATA LABEL ON THE APPLIANCE.

MODEL NUMBER	SERIAL NUMBER

## 6. WARRANTY

As a manufacturer of catering equipment, Victor Manufacturing Ltd offers warranty on all goods manufactured by the company and supplied by its United Kingdom Distributors.

Victor Manufacturing Ltd is renowned for its reliability and Victor Manufacturing Ltd provides on-site warranty in case of failure included in the purchase price, which covers the costs of spare parts and labour on your Victor Manufacturing Ltd goods from the date of invoice for a period of 24 months.

The Victor Manufacturing Ltd warranty does not affect any legal rights you have against the person who supplied your Victor Manufacturing Ltd goods or any other legal right against Victor Manufacturing Ltd under the laws of the United Kingdom – it is an addition to those rights.

All goods sold by Victor Manufacturing Ltd are subject to the Company's standard conditions of sale, a copy of which is available upon request.

Where the goods and components supplied by Victor Manufacturing Ltd are of the company's design and manufacture, Victor Manufacturing Ltd will make good any defects in those goods provided Victor Manufacturing Ltd liability will be limited to the following:

It is the purchaser's responsibility to prove that the unit is under warranty, e.g. receipt of purchase, invoice number, serial number, etc.

Damaged in transit claims must be reported in writing to the company within 3 days of receipt for your claim to be validated. Damaged goods will not be replaced or repaired if they have been used.

Victor Manufacturing Ltd must authorize all warranty repairs prior to the commencement of work. Work carried out on goods prior to authorization will not be covered nor will any resultant damage.

All warranty will be immediately invalidated if in the reasonable opinion of Victor Manufacturing Ltd, unauthorized repairs or modifications have been made to the goods, in the case of accident, misuse, or damage caused by improper installation

and altered or missing serial numbers. Victor Manufacturing Ltd will not provide warranty repairs if in our opinion the problem resulted from externally caused damage, use outside the goods specification, faults caused by inexperienced or non-approved repairers. All warranty will be immediately invalidated if installation of equipment is not in accordance with Victor Manufacturing Ltd installation instructions supplied.

Customer adjustments explained in the operating manual are not covered by Victor Manufacturing Ltd on-site warranty. Assistance can be received by contacting the warranty desk.

The liability of Victor Manufacturing Ltd and its appointed engineers are limited to the cost of repairs (parts and labour only) of the unit under warranty. Loss of food or other damages caused by faulty goods are not covered by the warranty.

No fault found warranty calls and installation errors are not covered under Victor Manufacturing Ltd warranty and will result in a charge being made for the callout and on-site labour for our appointed engineer. The Victor Manufacturing Ltd warranty does not cover the replacement of used consumables, or parts that require period adjustment or lubrication, unless the part is faulty.

You must have evidence that routine maintenance has been carried out by a qualified engineer in accordance with the instruction manual. This is of particular importance with refrigerated and gas fuelled appliances. Work made necessary by lack of routine maintenance or cleaning is not covered by this warranty and will be chargeable.

Victor Manufacturing Ltd parts and labour warranty is valid for the United Kingdom Mainland only. (Parts only all areas outside the United Kingdom Mainland.)

Some parts are automatically not covered by the Victor Manufacturing Ltd warranty (e.g. panels, glass, lamps, shelves, etc.) Many surface finishes including paint and plastic coated steel can be scratched and damaged if not properly cared for; such damage is not covered by the Victor Manufacturing Ltd warranty.

## **IF YOUR EQUIPMENT FAILS**

Refer to the instruction manual. If the problem still cannot be resolved, prepare a description of the fault you have.

Make sure you have your proof of purchase document (Invoice number or serial number) and the model number of the equipment that has failed.

Contact the warranty department on the following numbers:

Warranty Desk Telephone No:	01274 722125 (Office Hours)
Warranty Desk Fax No:	01274 307082 (Office Hours)
Warranty Desk Email address:	<a href="mailto:service@victormanufacturing.co.uk">service@victormanufacturing.co.uk</a>
Emergency Warranty Telephone No:	07876 898114 (All Other Times)

Warranty repairs are carried out between 9:00 a.m. and 5:00 p.m. Monday – Friday. Access required outside normal working hours may incur charges.

Registered Office:

Victor Manufacturing Ltd  
Lonsdale Works, Gibson Street, Bradford, BD3 9TF

