

SYNERGY DROP INS

REFRIGERATED BLOWN AIR DECK

MODEL NO: DRDK

The Synergy range of Refrigerated blown air decks are designed to be dropped into a counter surface to form a food servery. Four sizes in the range which accept 100mm deep GN1/1 size gastronorm containers. Each Synergy display is self-contained and easily installed.



DIMENSIONS

DRDK2: 850mm x 755mm x 540mm
DRDK3: 1177mm x 775mm x 540mm
DRDK4: 1504mm x 775mm x 540mm
DRDK5: 1831mm x 775mm x 540mm

ELECTRICAL CONNECTIONS

220V/240V; 1 phase 50Hz
DRDK2: 1.6kW loading
DRDK3: 1.6kW loading
DRDK4: 2.1kW loading
DRDK5: 2.4kW loading
Cable: 2 metres with 13 amp plug fitted

CONSTRUCTION

Top: Stainless steel
Exterior: Stainless steel
Interior: Stainless steel

CAPACITY

DRDK2: 2 x GN1/1
DRDK3: 3 x GN1/1
DRDK4: 4 x GN1/1
DRDK5: 5 x GN1/1

REFRIGERANT

R452a - zero ODP and low GWP refrigerant

OPERATING CONDITIONS

Designed to comply with the operating requirements of EN ISO 23953 - 2:2005 Performance level M1 (-1°C to +5°C) in Climate class 3 (25°C 60% RH 0.2m/s)
In use Victor refrigerated Synergy units will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C - 50% Relative humidity

PRODUCT FEATURES

- Designed for self or assisted service, with rear preparation shelf

GANTRY FEATURES

- Constructed from 50mm diameter bright polished stainless steel tube
- Fluorescent illumination to stainless steel light box
- Toughened glass screen and over shelf
- Digital temperature control and readout

WELL FEATURES

- 304 Stainless steel well - 170mm deep
- Load line indicator at 100mm to assist in the safe presentation of food
- Accepts GN1/1 gastronorm containers up to 100mm deep
- Completely removable well giving easy access for cleaning and maintenance

OPTIONS

- Front facing controls
- Polyethylene cutting board
600 x 250 x 40mm - Fits over rear preparation shelf



VICTOR

TELEPHONE
01274 722125

EMAIL
sales@victormfg.co.uk

WEBSITE
www.victoronline.co.uk