

MODULAR COUNTERS

JAMAICAN REFRIGERATED CONTACT COOLED WELL

MODEL NO: JCC

GN1/1 gastronorm compatible contact cooled refrigerated mobile salad well. Ideal for general purpose usage in all catering establishments, schools & colleges, residential care homes, pubs, hotels and cafes.



DIMENSIONS

JCC30: 1205mm x 670mm x 900mm

Well: 975mm x 530mm x 100mm

JCC40: 1535mm x 670mm x 900mm

Well: 1305mm x 530mm x 100mm

JCC50: 1860mm x 670mm x 900mm

Well: 1635mm x 530mm x 100mm

Standard counter top height is 900mm. Units can be manufactured with a working height of 800, 825, 850 or 875mm if required

ELECTRICAL CONNECTIONS

220V/240V; 1 phase 50Hz

1205 model: 1.5kW loading

1535 model: 1.5kW loading

1860 model: 1.5kW loading

Cable: 2 metres with 13 amp plug fitted

CONSTRUCTION

Top: Stainless steel

Exterior: Colour plastic coated steel or stainless steel

Interior: Stainless steel

CAPACITY

1205 model: 3 x GN1/1 x 100mm deep

1535 model: 4 x GN1/1 x 100mm deep

1860 model: 5 x GN1/1 x 100mm deep

REFRIGERANT

R452a - zero ODP and low GWP refrigerant

OPERATING CONDITIONS

In use refrigerated frost top units will have a surface temperature of -1°C to -5°C in ambient temperatures up to 25°C - 60% Relative humidity

PRODUCT FEATURES

- 304 grade stainless steel well - 100mm deep
- Completely sealed well giving for easy cleaning
- Automatic defrost & condense handling system
- Rear operator's side finished in stainless steel
- Open ambient cupboard to rear
- Four x 100mm swivel castors two braked

EXTRAS

- Gantries
- Tray slides
- Kick-plinths
- Push bars
- Corner bumpers
- Drop down end shelf
- Choice of colour finish
- Height adjustable feet instead of castors



VICTOR

TELEPHONE
01274 722125

EMAIL
sales@victormfg.co.uk

WEBSITE
www.victoronline.co.uk