RETAIL DISPLAYS

EVOLUTION REFRIGERATED ASSISTED SERVICE

MODEL NO: SER-E

Victor Evolution units are available in hot, ambient and chilled versions suitable for either assisted or self-service applications. They are perfectly suited for deli's, coffee shops, convenience stores and all food-to-go outlets.



DIMENSIONS

REAR LOADING DOORS

SER60E: 600mm x 750mm x 1350mm SER90E: 900mm x 750mm x 1350mm SER120E: 1200mm x 750mm x 1350mm

ELECTRICAL CONNECTIONS

220V/240V 1 phase 50Hz SER60E: 1.9kW loading SER90E: 2.8kW loading SER120E: 2.8kW loading

Cable: 2 metres with 13amp plug fitted

CONSTRUCTION

Constructed using durable bright polished and satin finish stainless steel with toughened glass screens. Choice of stainless steel, coloured plastic coated steel or wood laminate base fascia panels

REFRIGERANT

R452a - zero ODP and low GWP refrigerant

OPERATING CONDITIONS

Designed to comply with the operating requirements of EN ISO 23953 2:2005 Performance level M1 (-1°C to +5°C) in Climate class 3 (25°C 60%RH 0.2m/s)

PRODUCT FEATURES

- Special low height 1350mm high units - conform to TFL / Network rail maximum height for shop front equipment - Retail design standards - 2015
- Microprocessor based temperature control with automatic defrost and condensate handling system, for trouble free operation
- Illuminated display via integral LED lighting to each level
- Double glazed Eco gas filled thermo glass panels
- Three height adjustable 8mm toughened glass shelves. Shelves can be inclined by 10 degrees if required
- · Stainless steel removable recessed well for service access and cleaning
- Supplied on four low level castors
- · Integral ticket strip facility
- · Sliding rear doors

OPTIONS

- Shelf edge ticket strips
- · Castor covers satin finish stainless steel covers
- Base wrap options Standard product includes bright polished stainless or coloured plastic coated steel. Additional cost options of decorative laminated panels. Units are also available without a base wrap for self cladding or installing up to a counter front





sales@victormfg.co.uk /