

SYNERGY DROP INS

REFRIGERATED FROST TOP

MODEL NO: WDRCC

Frost top units are designed to be installed under or dropped into a suitable counter top. A thermal break must be provided around the stainless steel top to allow effective cooling. Supplied with wired control box.



DIMENSIONS

WDRCC2: 850mm x 660mm x 20mm
WDRCC3: 1177mm x 660mm x 20mm
WDRCC4: 1504mm x 660mm x 20mm
WDRCC5: 1831mm x 660mm x 20mm

ELECTRICAL CONNECTIONS

220V/240V; 1 phase 50Hz
WDRCC2: 1.5kW loading
WDRCC3: 1.5kW loading
WDRCC4: 1.5kW loading
WDRCC5: 1.5kW loading

Cable: 1.5 metres of cable and 13 amp plug

CONSTRUCTION

Top: Stainless steel
Exterior: Stainless steel
Interior: Stainless steel

CAPACITY

WDRCC2: 2 x GN1/1
WDRCC3: 3 x GN1/1
WDRCC4: 4 x GN1/1
WDRCC5: 5 x GN1/1

REFRIGERANT

R452a - zero ODP and low GWP refrigerant

OPERATING CONDITIONS

In use refrigerated frost top units will have a surface temperature of -1°C to -5°C in ambient temperatures up to 25°C - 60% Relative Humidity

PRODUCT FEATURES

- Designed for assisted service
- Illuminated on/off switch
- 304 Stainless steel top
- Accepts GN1/1 gastronorm containers

OPTIONS

- Heat transfer compound



VICTOR

TELEPHONE
01274 722125

EMAIL
sales@victormfg.co.uk

WEBSITE
www.victoronline.co.uk