

# Product information sheet

## SER90SP

A self-serve refrigerated display. It is perfectly suited for deli's coffee shops, convenience stores and all food-to-go outlets.

### **Product specifications:**

- 900mm x 750mm x 1350mm
- 220V/240V 1 phase 50Hz, 2.8Kw loading
- Cable: 2 metres with 13amp plug fitted

### **General product specifications:**

- Constructed using durable bright polished and satin finish stainless steel with toughened glass screens. Choice of stainless steel, coloured plastic coated steel or wood laminate base fascia panels.
- R290 refrigerant.
- Designed to comply with the operating requirements of EN ISO 23953. Performance level M2 (-1°C to +7°C) in Climate class 3 (25°C 60%RH 0.2m/s)

**Annual energy consumption (kWh/a) = 7708**

**Standard annual energy consumption (kWh/a) = 14466**

**Daily energy consumption = 21.12 kWh**

**Ambient conditions = CC3 (25c / 60%RH)**

**M = 9.1**

**N = 9.1**

**Temperature coefficient (C) = 1.15**

**Y = 1.98**

**P = 1.1**

### **Additional information:**

#### *Features:*

- Special low height 1350mm high units - conform m to TFL / Network rail maximum height for shop front equipment - Retail design standards - 2015
- Microprocessor based temperature control with automatic defrost and condensate handling system, for trouble free operation
- Illuminated display via integral LED lighting to each level
- Double glazed Eco gas filled thermo glass panels
- Three height adjustable 8mm toughened glass shelves. Shelves can be inclined by 10 degrees if required
- Stainless steel removable recessed well for service access and cleaning
- Supplied on four low level castors
- Integral ticket strip facility
- Hinged rear doors or solid stainless steel back

#### *Options:*

- Shelf edge ticket strips
- Pull down night blind
- Castor covers - satin finish stainless steel covers
- Base wrap options - Standard product includes bright polished stainless or coloured plastic coated steel. Additional cost options of decorative laminated panels. Units are also available without a base wrap for self cladding or installing up to a counter front

